

Page 1 of WELL CONSTRUCTION LOG BOREHOLE NUMBER **AS-15** ENSR Corporation, Inc. LOCATION PROJECT NAME 10411 Old Placerville Road Unocal No. 0813 122 Leslie Street Suite 210 PROJECT NUMBER Rancho Cordova, Ca. 95827 06940-264-120 Ukiah, California 916-362-7100 DRILLING CONTRACTOR / DRILLER LOGGED BY www.ensr.com Woodward Drilling Co. / V. Lenoard W. Speth BIT SIZE / BIT TYPE SAMPLING METHOD START-FINISH DATE DRILLING EQUIPMENT / METHOD Mobile B-81 / Hollow Stem Auger 8.25-Inch / Auger Mod. Split-Spoon 1/12/05 - 1/12/05 CASING MATL. / DIAMETER SLOT SIZE 40-Micron DIA. 1-Inch **PVC/1-Inch** TYPE Micro-Porous MATL. Plastic TOTAL LENGTH 1.75 **GW SURFACE** GROUND SURFACE **ELEVATION OF:** TOP OF WELL CASING **TOP & BOTTOM SCREEN** DATE Not Measured (A) (FT.) NORTHING EASTING LONGITUDE DATUM 8-Inch Connected Diameter to Sparge OVM Depth Graphic Blow Depth Sample Traffic Rated System Visual Description Values (feet) ΙĎ Log Counts (feet) Well Box (ppm) ASPHALT SURFACE CONCRETE \3.5 Inches thick
SILTY CLAY: medium brown, low plasticity, moist, very stiff. (CL-ML) 1-INCH DIAMETER FLUSH THREADED SCH 40 PVC RISER 5 5 6 10 12 5 18 AS-15-7 -NEAT CEMENT GROUT 10 10 1/20/05 13 15 ENSR CA.GDT SILT WITH SAND: medium brown with 17 blueish-green mottling, fine to medium grained sand, moist, very stiff. (ML) 477 AS-15-12 0813.GPJ 06940-264-UNOCAL POORLY GRADED SAND: blueish-green, 15 15 -BENTONITE non-plastic, wet, medium dense. (SP) 20 25 WELL GRADED SAND: blueish-green. 25 non-plastic, fine to coarse grained sand, saturated, POG 600 50 AS-15-17 dense. (SW) -No. 2/12 BORING SAND (FILTERPACK) 35 CONSTRUCTION/ SOIL 50 40-MICRON GRAVELY CLAY: blueish-green, low plasticity, 3/8 to 1 1/2 inch diameter gravel moist, hard. (GC) SPARGE POINT 20 AS-15-20 27 20 Bottom of borehole at 20 feet. WELL